DC BATTERY BACKUP BELT DRIVE WI-FI® GARAGE DOOR OPENER

Feature rich, offering ultimate garage protection.



SECURE

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0° SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

OUIFT AND RELIABLE

BELT DRIVE SYSTEM FOR POWERFUL, ULTRA-QUIET PERFORMANCE.

SOFT START/STOP FOR SMOOTH OPERATION.

DC MOTOR IS PURPOSEFULLY DESIGNED FOR QUIET, LONG-LASTING SERVICE.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR AND BELT, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

FREE MyQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

INCLUDED ACCESSORIES:

SMART CONTROL PANEL

LCD display enables simple programming and adjustment of settings.



3-BUTTON REMOTE CONTROL

Operates up to 3 openers or MyQ Light Accessories



893MAX

INTEGRATED BATTERY BACKUP

Powers up the opener when the power's out.



POWERFUL ADD-ONS:

AUTOMATIC GARAGE DOOR LOCK CAPABLE

Deadbolts the garage door automatically every time it closes.



REMOTE LIGHT CONTROL

Plug in any lamp to this device to control it with a smartphone or garage remote.



MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.





WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



DC BATTERY BACKUP BELT

MASTERFUL ENGINEERING.

MOTOR -



-12V DC

-53 RPM

MECHANICS -

- Automatic Thermal Protection

- Permanent Lubrication

- Steel Chassis, T-Rail and Trolley

and Environmental Conditions - Electronic Limits for Easy Setup

- Full Reinforced Belt Drive Mechanism

(63:1 Gear Reduction and Adjustable Door Arm) - Auto-Force Adjustment for Changing Weather

- DC Wi-Fi Logic Board with Built-In Surge Suppressor


(for Replacement Logic Boards, Order Part 050DCTWFLK)

-2 Lock Terminals Allow up to 2 Locks to Be Connected (Sold Separately)

POWER -



- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- -6' Power Cord (3-Prong)



Headroom Clearance Required: 2"

DRIVE WI-FI® GARAGE DOOR OPENER LiftMaster LO)

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Per second **SPEED**

> Per second for door

to move downward

STANDARD SPECS.

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200

Operating Temperature: -40°F to 150°F

- 3-Button Remote Control (893MAX)
- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding
- *Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880LMW)

- Timer-to-Close
- Program Remote Controls, Keypads
- and MyQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

'May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LIGHTING





for door

to move upward

- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

SHIPPING.

SHIPPING WEIGHT (in lbs.)









BACKUP



AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head (8550W)
- Smart Control Panel (880LMW)
- 3-Button Remote Control (893MAX)
- -The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Belt T-Rail

CARTON 3: 5.31" x 4.63" x 5.13"

- Battery (485LM)

LMGDENPG8550A 0617

CARTON 4 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock (841LM)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation[†]
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening

- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices





