

8 3 6 5 W - 2 6 7

# 1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

A complete, reliable solution with powerful performance.



## KEY FEATURES

**VALUE**  
Package

**CONSISTENT AND  
DEPENDABLE**  
Operation

**WI-FI**  
Built In

## RELIABLE

**1/2 HP AC MOTOR** IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

**CHAIN DRIVE SYSTEM** FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

**WARRANTY** LIFETIME MOTOR, 1-YEAR PARTS.

## SECURE

**SECURITY+ 2.0®** SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

**POSILOCK®** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

**ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

**THE PROTECTOR SYSTEM®** INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

## SMART

**BUILT-IN WI-FI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.

**MyQ TECHNOLOGY** ALLOWS USERS TO KNOW THEIR HOME IS SECURE.

**REAL-TIME ALERTS** INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

**MONITOR AND CONTROL** THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

## INCLUDED ACCESSORIES:

### MULTI-FUNCTION CONTROL PANEL®

Turns on garage door opener lights from inside the garage.



882LMW

### (2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ Light Accessories each.



893LM

### WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



877LM

## POWERFUL ADD-ONS:

### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

### REMOTE LIGHT CONTROL

Enables home lighting control through a garage remote or a smartphone.



825LM

### REMOTE LIGHT SWITCH

Replaces an existing wall switch to enable home lighting control with a garage remote or smartphone.



823LM

### DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

PRODUCT GUIDE 8365W-267

1/2 HP AC CHAIN DRIVE WI-FI  
GARAGE DOOR OPENER

**LiftMaster®**

# MASTERFUL ENGINEERING.

## MOTOR

- 1/2 Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

## POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

## MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (16:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **AC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)



## DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	10'	10'

Headroom Clearance Required: 2"

**7"**  
Per second for door to move upward

**7"**  
Per second for door to move downward

# STANDARD SPECS.

## SECURITY

### RADIO CONTROLS

Operating Range: **~200'**  
Operating Temperature: -35°F to 150°F

- SECURITY+ 2.0®**  
(2) 3-Button Remote Controls (893LM) and Wireless Keyless Entry (877LM)
- Remote Controls: 310, 315 and 390 MHz Tri-Band\*
  - Keyless Entry: 310, 315 and 390 MHz Tri-Band\*
  - Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
  - Anti-Burglary Coding
- \*Tri-band on Security+ 2.0 coding only.

- ENCRYPTED CONTROLS**  
Multi-Function Control Panel® (882LMW)
- Program Remote Controls
  - Maintenance Alert System
  - Easy Wi-Fi Setup

## SMART

### MyQ® RADIO

**902-928 MHz**  
50-Channel FHSS  
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

### HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

## ELECTRICAL

### LIGHTING



- Max. 2 100-Watt Lightbulbs
- Solid-State Light Delay
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

# SHIPPING.

**SHIPPING WEIGHT**  
(in lbs.)



### CARTONS (2)

- CARTON 1:** 20" x 12" x 10"  
 - Garage Door Opener Head (8365W)  
 - Multi-Function Control Panel (882LMW)  
 - (2) 3-Button Remote Controls (893LM)  
 - Wireless Keyless Entry (877LM)  
 - The Protector System® Safety Reversing Sensors
- CARTON 2:** 10'4" x 5" x 5" (for 7' Rail)  
 - Assembled Solid-Steel Chain T-Rail

# CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation (with Select Accessories)<sup>†</sup>
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices

